

Aperlan Poka-Yoke

Aperlan Poka-Yoke Agent A

SECTION 1: Identification of the substance/mixture and company

1.1 Product identifier

Product code: 41010058
Unique Formula Identifier (UFI): DQG0-T047-S00E-V1FW
Name: Aperlan Poka-Yoke Agent A

1.2 Product uses

Disinfectant for medical device. Restricted to professional users.

1.3 Supplier

Details of the supplier of the Safety Data Sheet.

Supplier:
Getinge Disinfection AB
Ljungadalsgatan 11
352 46 Växjö
SWEDEN
Phone: +46 (0) 10 335 98 00
Web: www.getinge.com
E-mail: info@getinge.com

Supplier Australia
Getinge Australia Pty Ltd
Level 7, 11 Help St
Chatswood NSW 2067 Australia
Telephone: 1800 438 464

Supplier New Zealand
Getinge Australia (NZ Branch)
Building A, Ground Floor, Unit D
Ellerslie, Auckland 1051 New Zealand
Telephone: +64 9 272 9039

1.4 Emergency telephone number

For emergency event of spillage, inhalation or ingestion of products, please contact the emergency hotline:

EU: +44 (0) 123 523 96 70
Australia: +61 280 144 558
Japan: +81 345 789 341
China: +86 105 100 30 39
Middle East: +44 (0) 123 523 96 71
New Zealand: +64 992 914 83

SECTION 2: Hazards identification (undiluted product)

2.1 Classification of the substance or mixture

New Zealand EPA Approval No: Additives, Process Chemicals and Raw Materials (Corrosive) Group Standard 2020 – HSR002491

Classification (REGULATION (EC) No 1272/2008)

H272	Oxidizing liquids, Category 2. May intensify fire; oxidizer.
H290	Corrosive to metals, Category 1. May be corrosive to metals.
H302	Acute toxicity, Category 4. Harmful if swallowed.
H332	Acute toxicity, Category 4. Harmful if inhaled.
H314	Skin corrosion, Category 1A. Causes severe skin burns and eye damage.
H318	Serious eye damage, Category 1. Causes serious eye damage.
H335	Specific target organ toxicity - single exposure, Category 3, Respiratory system. May cause respiratory irritation.
H410	Long-term (chronic) aquatic hazard, Category 1. Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms:



Signal word:

Danger

Hazard statements:

H272 May intensify fire; oxidizer.
H290 May be corrosive to metals
H302 + H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.
H410 Very toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements:

EUH071 Corrosive to the respiratory tract.

Precautionary statements:

P220 Keep away from clothing and other combustible materials.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P310 Immediately call a POISON CENTER/ doctor.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403 + P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

79-21-0 Peracetic acid

7722-84-1 Hydrogen peroxide

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

No special risks known.

SECTION 3: Composition/information on ingredients

Chemical nature: Solution of the following substances

Chemical name	CAS number EC-No. Index-No. Registration number	Concentration (% w/w)	Classification
Hydrogen peroxide	7722-84-1 231-765-0 008-003-00-9 01-2119485845-22-XXXX	>= 20 - < 25	Ox. Liq. 1; H271 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 specific concentration limit Ox. Liq. 1; H271 >= 70% Ox. Liq. 2; H272 50 - < 70% Skin Corr. 1A; H314 >= 70% Skin Corr. 1B; H314 50 - < 70% Skin Irrit. 2; H315 35 - < 50% Eye Dam. 1; H318 8 - < 50% Eye Irrit. 2; H319 5 - < 8% STOT SE 3; H335 >= 35%
Acetic acid	64-19-7 200-580-7 607-002-00-6 01-2119475328-30-XXXX	>= 5 - < 10	Flam. Liq. 3; H226 Skin Corr. 1A; H314 Eye Dam. 1; H318 specific concentration limit Skin Corr. 1A; H314 >= 90% Skin Corr. 1B; H314 25 - < 90% Skin Irrit. 2; H315 10 - < 25% Eye Irrit. 2; H319 10 - < 25%
Peracetic acid	79-21-0 201-186-8 607-094-00-8 01-2119531330-56-XXXX	>= 3 - < 5	Flam. Liq. 3; H226 Org. Perox. D; H242 Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10 specific concentration limit STOT SE 3; H335 >= 1%

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice:	Take off all contaminated clothing immediately. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
Skin contact:	Wash off immediately with plenty of water. Call a physician immediately.
Inhalation:	Move the victim to fresh air and keep him calm. If symptoms persist, call a physician.
Ingestion:	Do NOT induce vomiting. Rinse mouth with water. Give small amounts of water to drink. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms:	Treat symptomatically.
Risks:	Harmful if swallowed or if inhaled. Causes serious eye damage. Corrosive to the respiratory tract. Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Suitable Extinguishing media

Dry powder, Foam and Water spray jet.

5.2 Unsuitable Extinguishing media

Carbon dioxide (CO₂)

Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products: Oxygen.

5.3 Special hazards arising from the substance or mixture

Cool down closed containers exposed to fire with water spray.

5.4 Advice for firefighters

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Do not breathe vapor.

Remove all sources of ignition.

6.2 Environmental precautions

Avoid subsoil penetration.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material.

Unsuitable material for picking up:

Absorbent material, organic

Kieselguhr

Sawdust

Keep in suitable, closed containers for disposal.

Clean contaminated surface thoroughly.

Flush with water.

6.4 Reference to other sections

Observe the advice given in sections 8 and 13.

SECTION 7: Handling and storage

After opening, use within: 2 months.

7.1 Precautions for safe handling

Provide sufficient air exchange and/or exhaust in work rooms. Handle and open container with care. Never return unused material to storage receptacle.

Keep away from sources of ignition - No smoking. Keep away from combustible material. May cause or intensify fire; oxidizer.

When using do not eat or drink. Take off all contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in the original container. Suitable container and packaging materials for safe storage Plastic container of HDPE Polyethylene glass Unsuitable materials for containers Metals Store in a receptacle equipped with a vent. Keep in a bonded area.

Keep away from heat. Keep away from direct sunlight. Store in cool place. Do not keep the container sealed. Store in up-right position only. Recommended storage temperature: 5 - 30°C.

Do not store together with metals.

Do not store together with alkalis.

Do not store together with reducing agents.

Do not store together with combustible substances.

7.3 Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Hydrogen peroxide CAS-No. 7722-84-1

Value type (Form of exposure)	Control parameters	Basis
TWA	1 ppm 1.4 mg/m ³	GB EH40
STEL	2 ppm 2.8 mg/m ³	GB EH40
PEL	1.25 mg/m ³	Biocide dossier
STEL	1.25 mg/m ³	Biocide dossier

Acetic acid CAS-No. 64-19-7

Value type (Form of exposure)	Control parameters	Basis
STEL	20 ppm 50 mg/m ³	GB EH40
TWA	10 ppm 25 mg/m ³	GB EH40
TWA	10 ppm 25 mg/m ³	2017/164/EU
STEL	20 ppm 50 mg/m ³	2017/164/EU

Peracetic acid CAS-No. 79-21-0

Value type (Form of exposure)	Control parameters	Basis
PEL	0.16 ppm 0.5 mg/m ³	Biocide dossier
STEL	0.16 ppm 0.5 mg/m ³	Biocide dossier

Derived No Effect Level (DNEL)

Hydrogen peroxide

End Use	Exposure routes	Potential health effects	Value
Workers	Inhalation	Long-term local effects	1.4 mg/m ³

Acetic acid

End Use	Exposure routes	Potential health effects	Value
Workers	Inhalation	Acute local effects	25 mg/m ³
Workers	Inhalation	Long-term local effects	25 mg/m ³

Predicted No Effect Concentration (PNEC)

Hydrogen peroxide

Environmental Compartment

Value

Fresh water	0.0126 mg/l
Marine water	0.0126 mg/l
Effects on waste water treatment plants	4.66 mg/l
Fresh water sediment	0.047 mg/kg
Marine sediment	0.047 mg/kg
Soil	0.0023 mg/kg

Acetic acid

Environmental Compartment

Value

Fresh water	3.058 mg/l
Marine water	0.306 mg/l
Fresh water sediment	11.36 mg/kg
Marine sediment	1.136 mg/kg
Intermittent use/release	30.58 mg/l
Soil	0.478 mg/kg
Effects on waste water treatment plants	85 mg/l

Peracetic acid

Environmental Compartment

Value

Fresh water	0.0069 µg/l
Marine water	0.069 µg/l
Effects on waste water treatment plants	0.051 mg/l
Effects on terrestrial organisms	0.282 mg/kg

8.2 Exposure controls

Engineering measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protective equipment

Eye protection:	Safety glasses with side-shields conforming to EN166 Face-shield
Hand protection:	Directive: The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Remarks: Prolonged contact: Nitrile rubber gloves e.g. Camatril (>120 Min., layer thickness: 0.40 mm) or butyl rubber gloves e.g. Butoject (>480 Min., layer thickness: 0.70 mm) made by KCL or gloves from other manufacturers offering the same protection. Splash protection: disposable nitrile rubber gloves e.g. Dermatril (layer thickness: 0.11 mm) made by KCL or gloves from other manufacturers offering the same protection.
Skin and body protection:	Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: ▪ Chemical resistant apron ▪ Boots ▪ Neoprene
Respiratory protection:	If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time. Combination filter: A2B2E2K2 Hg NO P3 P D/ CO 20 P3 R D
Protective measures:	Do not breathe vapor. Avoid contact with skin and eyes.
Personal protective equipment:	Exact PPE requirements should be determined from a specific risk assessment of the processes being carried out. 

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Liquid
Color:	Colourless
Odor:	Vinegar-like
Odor Threshold:	Not determined
pH:	<1 (20°C)
Melting point/freezing point:	< -26°C
Decomposition temperature:	No data available
Boiling point/boiling range:	Approx. 100°C
Flash point:	N/A
Evaporation rate:	No data available
Flammability (solid, gas):	N/A
Upper explosion limit:	No data available
Lower explosion limit:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Relative density:	1.12 g/cm ³ (20°C)
Water solubility:	Completely soluble
Partition coefficient: noctanol/water	N/A
Auto-ignition temperature:	No data available
Viscosity, dynamic:	No data available
Explosive properties:	Not explosive
Oxidizing properties:	Oxidizing

9.2 Other information

Metal corrosion rate: Corrosive to metals Aluminum and Mild steel.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

Self-Accelerating decomposition temperature (SADT): >60°C.

10.3 Possibility of hazardous reactions

Keep away from combustible material. To avoid thermal decomposition, do not overheat.

10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Reducing agents, Acid chlorides, Strong acids and strong bases, Aldehydes and Metals.

10.6 Hazardous decomposition products

Oxygen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product

Acute oral toxicity: Acute toxicity estimate: 1,043 mg/kg
Method: Calculation method

Acute inhalation toxicity: Acute toxicity estimate: 3.93 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity: Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components

Hydrogen peroxide

Acute oral toxicity: LD50 (Rat): 801 mg/kg
Remarks: Harmful if swallowed.

Acute inhalation toxicity: Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, Annex VI, Table 3.1

Acute dermal toxicity: LD50 (Rat): 6,500 mg/kg

Acetic acid

Acute oral toxicity: LD50 (Rat): 3,310 mg/kg

Acute inhalation toxicity: LC50 (Rat): > 39.8 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity: LD50 (Rabbit): > 2,000 mg/kg

Peracetic acid

Acute oral toxicity: LD50: 300 - 2,000 mg/kg
Assessment: Harmful if swallowed.

Acute inhalation toxicity: LC50: 1 - 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Harmful if inhaled.

Acute dermal toxicity: LD50: 1,000 - 2,000 mg/kg
Assessment: Harmful if inhaled.

11.1.2 Skin corrosion/irritation

Product

Assessment: Causes severe burns

Components

Hydrogen peroxide

Species:	Rabbit
Result:	Corrosive after 3 minutes or less of exposure

Acetic acid

Species:	Rabbit
Method:	OECD Test Guideline 404
Result:	Corrosive after 3 minutes or less of exposure

Peracetic acid

Species:	Rabbit
Method:	OECD Test Guideline 404
Result:	Corrosive after 3 minutes or less of exposure

11.1.3 Serious eye damage/eye irritation

Product

Assessment: Causes serious eye damage

Components

Hydrogen peroxide

Species:	Rabbit
Result:	Irreversible effects on the eye

Acetic acid

Species:	Rabbit
Method:	OECD Test Guideline 405
Result:	Irreversible effects on the eye

Peracetic acid

Species:	Rabbit
Result:	Irreversible effects on the eye

11.1.4 Respiratory or skin sensitization

Components

Hydrogen peroxide

Species:	Guinea pig
Result:	Did not cause sensitization on laboratory animals

Acetic acid

Result:	No data available
---------	-------------------

Peracetic acid

Species:	Mouse
Result:	Did not cause sensitization on laboratory animals.
Remarks:	Substance is not considered to be potential skin sensitizer.

11.1.5 Germ cell mutagenicity

Components

Hydrogen peroxide

Genotoxicity in vitro:	Test Type: Ames test Result: negative
Genotoxicity in vivo:	Test Type: in vivo assay Result: Non mutagenic

Acetic acid

Genotoxicity in vitro:	Test Type: Ames test Result: negative
------------------------	--

Peracetic acid

Germ cell mutagenicity Assessment:	Germ cell effects are not relevant., The substance has been tested for mutagenicity and other types of genotoxic effects in vitro and in vivo experiments and is evaluated as being non-mutagenic.
------------------------------------	--

11.1.6 Carcinogenicity

Components

Hydrogen peroxide

Carcinogenicity Assessment:	Animal testing did not show any carcinogenic effects.
-----------------------------	---

Acetic acid

Carcinogenicity Assessment:	Animal testing did not show any carcinogenic effects.
-----------------------------	---

Peracetic acid

Carcinogenicity Assessment:	No structural alerts for carcinogenicity were found.
-----------------------------	--

11.1.7 Reproductive toxicity

Components

Hydrogen peroxide

Reproductive toxicity - Assessment: Animal testing did not show any effects on fertility.

Acetic acid

Reproductive toxicity - Assessment: Animal testing did not show any effects on fertility.

Peracetic acid

Effects on foetal development: Species: Rat
Application Route: Oral
General Toxicity Maternal: NOAEL: 100 mg/l
Teratogenicity: NOAEL F1: 100 mg/l

Reproductive toxicity - Assessment: Animal testing did not show any effects on fertility.

11.1.8 STOT - single exposure

Components

Hydrogen peroxide

Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

Acetic acid

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Peracetic acid

Assessment: May cause respiratory irritation.

11.1.9 STOT - repeated exposure

Components

Hydrogen peroxide

Assessment: No data available

Acetic acid

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Peracetic acid

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

11.1.10 Repeated dose toxicity

Components

Hydrogen peroxide

Species:	Rat
NOAEL:	26 mg/kg
Application Route:	Oral
Exposure time:	3 months
Remarks:	No adverse effect has been observed in chronic toxicity tests. No adverse effect has been observed in chronic toxicity tests.

Species:	Rat
NOAEL:	0.0029 mg/l
Application Route:	Inhalation (vapor)
Method:	OECD Test Guideline 407

Acetic acid

Species:	Rat
NOAEL:	1,800 mg/kg
Application Route:	Oral
Exposure time:	14-days

Peracetic acid

Species:	Rat
NOAEL:	15 mg/kg
Exposure time:	90-day
Remarks:	No adverse effect has been observed in sub chronic toxicity tests.

11.1.11 Aspiration toxicity

Not classified based on available information.

11.1.12 Further information

Product

Remarks:	Description of possible hazardous to health effects is based on experience and/or toxicological characteristics of several components. If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.
----------	--

SECTION 12: Ecological information

12.1 Toxicity

Components

Hydrogen peroxide

Toxicity to fish:	LC50 (Fish): 16.4 - 37.4 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates:	EC50 (Daphnia pulex (Water flea)): 2.4 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants:	ErC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l Exposure time: 72 h NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity):	NOEC: 0.63 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)

Acetic acid

Toxicity to fish:	LC50 (Gambusia affinis (Mosquito fish)): 251 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates:	EC50 (Daphnia magna): 95 mg/l Exposure time: 24 h
Toxicity to algae/aquatic plants:	EC100 (Euglena gracilis): 720 mg/l Exposure time: 0.25 h

Peracetic acid

Toxicity to fish:	LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.1 mg/l Exposure time: 96 h Test Type: semi-static test
Toxicity to daphnia and other aquatic invertebrates:	EC50 (Daphnia magna): 0.73 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae/aquatic plants:	NOEC (Pseudokirchneriella subcapitata (green algae)): 0.061 mg/l Exposure time: 72 h Test Type: static test
M-Factor (Acute aquatic toxicity):	1
Toxicity to fish (Chronic toxicity):	NOEC: 0.00069 mg/l Exposure time: 33 d Species: Danio rerio (zebra fish)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity):	NOEC: 0.0121 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)
M-Factor (Chronic aquatic toxicity):	10

12.2 Persistence and degradability

Components

Hydrogen peroxide

Biodegradability:	Result: Totally biodegradable Method: OECD Test Guideline 301
-------------------	--

Acetic acid

Biodegradability:	Result: Totally biodegradable Method: OECD 301D / EEC 84/449 C6
-------------------	--

Peracetic acid

Biodegradability:	Result: Readily biodegradable. Method: OECD Test Guideline 301
-------------------	---

12.3 Bioaccumulative potential

Components

Hydrogen peroxide

Bioaccumulation:	Remarks: Does not bioaccumulate
------------------	---------------------------------

Partition coefficient: noctanol/water: log Pow: -1.57

Acetic acid

Bioaccumulation:	Remarks: Bioaccumulation is unlikely.
------------------	---------------------------------------

Peracetic acid

Bioaccumulation:	Remarks: Does not bioaccumulate
------------------	---------------------------------

Partition coefficient: noctanol/water: log Pow: -0.26 (20 °C)
Method: Calculated value

12.4 Mobility in soil

Components

Hydrogen peroxide

Mobility:	Medium: Water Remarks: Hydrolyses readily.
-----------	---

Acetic acid

Mobility:	Remarks: No data available.
-----------	-----------------------------

Peracetic acid

Mobility:	Medium: Water Remarks: Hydrolyses readily.
-----------	---

12.5 Results of PBT and vPvB assessment

Product

Assessment:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
-------------	--

12.6 Other adverse effects

Product

Endocrine disrupting potential:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
---------------------------------	---

Additional ecological information:	No data is available on the product itself
------------------------------------	--

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product:	Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
----------	---

Contaminated packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.
-------------------------	--

SECTION 14: Transport information

14.1 UN number

ADR/IMDG/IATA: UN 3149.

14.2 UN proper shipping name

ADR/IMDG: HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED

IATA: Hydrogen peroxide and peroxyacetic acid mixture stabilized

14.3 Transport hazard class(es)

ADR/IMDG/IATA: 5.1

14.4 Packing group

ADR

Packing group: II

Classification Code: OC1

Hazard Identification Number: 58

Labels: 5.1 (8)

Tunnel restriction code: (E)

IMDG

Packing group: II

Labels: 5.1 (8)

EmS Code: F-H, S-Q

IATA (Cargo)

Packing instruction (cargo aircraft): 554

Packing instruction (LQ): Y540

Packing group: II

Labels: Oxidizer, Corrosive

IATA (Passenger)

Packing instruction (passenger aircraft): 550

Packing instruction (LQ): Y540

Packing group: II

Labels: Oxidizer, Corrosive

14.5 Environmental hazards

ADR

Not environmentally hazardous

IMDG

Not marine pollutant

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

N/A for product as supplied.

SECTION 15: Regulatory information

New Zealand EPA Approval No: Additives, Process Chemicals and Raw Materials (Corrosive) Group Standard 2020 – HSR002491

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59): N/A

Regulation (EC) No 850/2004 on persistent organic pollutants: N/A

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P8	OXIDIZING LIQUIDS AND SOLIDS	50 t	200 t

Other Regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values.

15.2 Chemical safety assessment

Exempt

SECTION 16: Other information

16.1 Full text of H-Statements

H226:	Flammable liquid and vapor.
H242:	Heating may cause a fire.
H271:	May cause fire or explosion; strong oxidizer.
H301:	Toxic if swallowed.
H302:	Harmful if swallowed.
H312:	Harmful in contact with skin.
H314:	Causes severe skin burns and eye damage.
H318:	Causes serious eye damage.
H330:	Fatal if inhaled.
H332:	Harmful if inhaled.
H335:	May cause respiratory irritation.
H400:	Very toxic to aquatic life.
H410:	Very toxic to aquatic life with long lasting effects.
H412:	Harmful to aquatic life with long lasting effects.

16.2 Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Eye Dam.	Serious eye damage
Flam. Liq.	Flammable liquids
Org. Perox.	Organic peroxides
Ox. Liq.	Oxidizing liquids
Skin Corr.	Skin corrosion
STOT SE	Specific target organ toxicity - single exposure
2017/164/EU	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / STEL	Short term exposure limit
2017/164/EU / TWA	Limit Value - eight hours
GB EH40 / TWA	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50% of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

16.3 Further information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No. 1272/2008.

Ox. Liq. 2 H272	Based on product data or assessment
Met. Corr. 1, H290	Based on product data or assessment
Acute Tox. 4 H302	Calculation method.
Acute Tox. 4 H332	Calculation method.
Skin Corr. 1B, H314	Calculation method.
Eye Dam. 1, H318	Calculation method.
STOT SE 3 H335	Calculation method.
Aquatic Chronic 1, H410	Calculation method.

2024-06-26

This product should be stored, handled and used in accordance with good industrial practice and in conformity with legal regulations. The information in this data sheet is based on the present state of our knowledge and is intended to describe products from the point of view of safety requirements and thus should not be construed as guaranteeing specific properties. It is for users to satisfy themselves of the suitability of this product for their own applications.