



SAFETY DATA SHEET

Tulp Operations Australia Pty Ltd

Product name: MOLYKOTE® G-Rapid Plus Paste Spray

Issue Date: 11.10.2023

Print Date: 18.10.2023

Tulp Operations Australia Pty Ltd encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product name: MOLYKOTE® G-Rapid Plus Paste Spray

Recommended use of the chemical and restrictions on use

Identified uses: Lubricants and lubricant additives

COMPANY IDENTIFICATION

Tulp Operations Australia Pty Ltd
15 Blackman Crescent
SOUTH WINDSOR NSW 2756
AUSTRALIA

Customer Information Number: +61 2 9923 6111

SDSQuestion-AP@dupont.com

EMERGENCY TELEPHONE NUMBER

Local Emergency Contact: (02) 9037 2994

AUSTRALIA AND NEW ZEALAND CONTACTS

Getinge Australia Pty Ltd
Suite 701, Level 7
11 Help Street
Chatswood NSW 2067 Australia
Tel: 1800 438 464

Getinge Australia (New Zealand Branch)
600 Great South Road
Building A, Ground Floor, Unit D
Ellerslie, Auckland 1051 NZ
Tel: +64 9 272 9039

Emergency Tel:
Australia: 1800 74234
New Zealand: +64 9 272 9039

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification

Aerosols	: Category 1
Serious eye damage/eye irritation	: Category 1
Specific target organ toxicity - single exposure	: Category 3 (Central nervous system)
Short-term (acute) aquatic hazard	: Category 3
Long-term (chronic) aquatic hazard	: Category 3

GHS label elements

Hazard pictograms



Signal word: **DANGER!**

Hazard statements

Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes serious eye damage.
May cause drowsiness or dizziness.
Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing mist.
Avoid breathing spray.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear eye protection/ face protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Other hazards

No data available

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS, IN ACCORDANCE WITH SCHEDULE 8

This product is a mixture.

Component	CASRN	Concentration
Butane (containing < 0.1% butadiene)	106-97-8	>= 30.0 - < 50.0 %
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 25.0 - < 30.0 %
White mineral oil (petroleum)	8042-47-5	>= 10.0 - < 20.0 %
Molybdenum disulfide	1317-33-5	>= 1.0 - < 10.0 %
Calcium hydroxide	1305-62-0	>= 3.0 - < 10.0 %

Graphite

7782-42-5

>= 1.0 - < 10.0 %

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. If excessive inhalation of mineral oil mist is suspected, observe for lung injury (lipoid pneumonia). Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIREFIGHTING MEASURES

Hazchem Code

None Allocated

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical

Unsuitable extinguishing media: Do not use direct water stream.

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides Sulphur oxides Metal oxides

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance. May form explosive mixtures in air. Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Vapours may form explosive mixtures with air.

Advice for firefighters

Fire Fighting Procedures: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. **EXPLOSION HAZARD.** Fight advanced fires from a protected location. Do not use a solid water stream as it may scatter and spread fire.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

Precautions for safe handling: Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste

and minimize release to the environment. Close valve after each use and when empty. Do NOT change or force fit connections. Open the valves slowly to prevent pressure surges. Handle in accordance with good industrial hygiene and safety practice. Do not spray on an open flame or other ignition source.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Do not store with the following product types: Self-reactive substances and mixtures. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Unsuitable materials for containers: None known.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Butane (containing < 0.1% butadiene)	ACGIH	STEL	1,000 ppm
	Further information: EX: Explosion hazard: the substance is a flammable asphyxiant or excursions above the TLV® could approach 10% of the lower explosive limit.; CNS impair: Central Nervous System impairment		
	AU OEL	TWA	1,900 mg/m3 800 ppm
Naphtha (petroleum), hydrotreated heavy	AU OEL	TWA	900 mg/m3
White mineral oil (petroleum)	ACGIH	TWA Inhalable particulate matter	5 mg/m3
	Further information: URT irr: Upper Respiratory Tract irritation; A4: Not classifiable as a human carcinogen		
Molybdenum disulfide	ACGIH	TWA Inhalable particulate matter	10 mg/m3 , Molybdenum
	ACGIH	TWA Respirable particulate matter	3 mg/m3 , Molybdenum
	AU OEL	TWA	10 mg/m3 , Molybdenum
Calcium hydroxide	ACGIH	TWA	5 mg/m3
	AU OEL	TWA	5 mg/m3
Graphite	ACGIH	TWA Respirable particulate matter	2 mg/m3
	Further information: pneumoconiosis: Pneumoconiosis		
	AU OEL	TWA Respirable dust	3 mg/m3

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

This material contains a simple asphyxiant which may displace oxygen. Insure adequate ventilation to prevent an oxygen deficient atmosphere.

The minimum requirement of 19.5% oxygen at sea level (148 torr O₂, dry air) provides an adequate amount of oxygen for most work assignments.

Exposure controls

Engineering measures: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use chemical resistant gloves classified under standard AS/NZS 2161.10: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to AS/NZS 2161.10) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to AS/NZS 2161.10) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

Other Information: Selection and use of personal protective equipment should be in accordance with the recommendations in one or more of the relevant Australian/New Zealand Standards, including:

AS/NZS 1336: Eye and face protection – Guidelines.

AS/NZS 1337: Personal eye protection - Eye and face protectors for occupational applications.

AS/NZS 1715: Selection, use and maintenance of respiratory protective equipment.

AS/NZS 2161: Occupational protective gloves.

AS/NZS 2210: Occupational protective footwear.

AS/NZS 4501: Occupational protective clothing Set

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Aerosol containing a dissolved gas
Color	black
Odor	solvent-like
Odor Threshold	No data available
pH	Not applicable
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	Not applicable
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	Extremely flammable aerosol.
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	0.74
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	Not applicable
Kinematic Viscosity	Not applicable
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde. Vapours may form explosive mixture with air. Extremely flammable aerosol.

Can react with strong oxidizing agents. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours. Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde. Vapours may form explosive mixture with air. Extremely flammable aerosol.

Conditions to avoid: Heat, flames and sparks.

Incompatible materials: Oxidizing agents

Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, Rabbit, > 2,000 mg/kg Estimated.

Acute inhalation toxicity

If material is heated or sprayed to generate aerosols or mists, concentrations may be attained that are sufficient to cause respiratory irritation and other effects. May cause central nervous system effects. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). Excessive exposure to mineral oil mist may cause lung injury (lipoid pneumonia).

As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause skin irritation with local redness.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on information for component(s):

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

Contains component(s) which did not cause cancer in laboratory animals.

Teratogenicity

Contains component(s) which did not cause birth defects in laboratory animals.

Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:**Butane (containing < 0.1% butadiene)****Acute inhalation toxicity**

LC50, Rat, 4 Hour, vapour, 658 mg/l

Naphtha (petroleum), hydrotreated heavy**Acute inhalation toxicity**

Based on data from similar materials LC50, Rat, 4 Hour, vapour, > 4,951 mg/m³

White mineral oil (petroleum)**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 5 mg/l OECD Test Guideline 403

Molybdenum disulfide**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 2.82 mg/l No deaths occurred at this concentration.

Calcium hydroxide**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 6.04 mg/l OECD Test Guideline 436

Graphite**Acute inhalation toxicity**

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. LC50, Rat, 4 Hour, dust/mist, > 2 mg/l OECD Test Guideline 403

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Ecotoxicity**Butane (containing < 0.1% butadiene)****Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

Naphtha (petroleum), hydrotreated heavy**Acute toxicity to fish**

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

Based on data from similar materials

LL50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 10 - 30 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

Based on data from similar materials

EL50, Daphnia magna (Water flea), 48 Hour, > 22 - 46 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

Based on data from similar materials

EL50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 1,000 mg/l, OECD Test Guideline 201

Based on data from similar materials

NOELR, Pseudokirchneriella subcapitata (green algae), 72 Hour, 1 mg/l, OECD Test Guideline 201

White mineral oil (petroleum)**Acute toxicity to fish**

Information given is based on data obtained from similar substances.

LC50, Leuciscus idus (Golden orfe), 96 Hour, > 10,000 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

Information given is based on data obtained from similar substances.

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 100 mg/l, OECD Test Guideline 201

Chronic toxicity to aquatic invertebrates

Based on data from similar materials

NOEC, Daphnia magna (Water flea), 21 d, 10 mg/l

Molybdenum disulfide

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For similar material(s):

LC50, Fish, 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates

Based on data from similar materials

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

Acute toxicity to algae/aquatic plants

Based on data from similar materials

ErC50, algae, 72 Hour, Growth rate, > 100 mg/l

Toxicity to bacteria

EC50, 30 Hour, Respiration rates., > 100 mg/l

Chronic toxicity to fish

Based on data from similar materials

NOEC, Fish, 34 d, > 10 mg/l

Chronic toxicity to aquatic invertebrates

Based on data from similar materials

NOEC, Daphnia magna, 21 d, > 10 mg/l

Calcium hydroxide

Acute toxicity to algae/aquatic plants

EC50, Raphidocelis subcapitata (freshwater green alga), 72 Hour, 184.47 mg/l, OECD Test Guideline 201

NOEC, Raphidocelis subcapitata (freshwater green alga), 72 Hour, 48 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, 3 Hour, 300.4 mg/l, OECD Test Guideline 209

Chronic toxicity to aquatic invertebrates

NOEC, 14 d, 32 mg/l

Graphite

Acute toxicity to fish

No toxicity at the limit of solubility

LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

No toxicity at the limit of solubility

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Raphidocelis subcapitata (freshwater green alga), 72 Hour, > 100 mg/l, OECD Test Guideline 201
NOEC, Raphidocelis subcapitata (freshwater green alga), 72 Hour, >= 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, 3 Hour, > 1,012.5 mg/l, OECD Test Guideline 209

Persistence and degradability**Butane (containing < 0.1% butadiene)**

Biodegradability: Material is expected to be readily biodegradable.

Theoretical Oxygen Demand: 3.58 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 49 Hour

Method: Estimated.

Naphtha (petroleum), hydrotreated heavy

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Based on data from similar materials 10-day Window: Pass

Biodegradation: 89 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

White mineral oil (petroleum)

Biodegradability: Not readily biodegradable. Information given is based on data obtained from similar substances.

Biodegradation: 31 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Theoretical Oxygen Demand: 3.50 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 1.291 d

Method: Estimated.

Molybdenum disulfide

Biodegradability: Biodegradability is not applicable to inorganic substances.

Graphite

Biodegradability: Not applicable

Bioaccumulative potential**Butane (containing < 0.1% butadiene)**

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 2.89 Measured

Naphtha (petroleum), hydrotreated heavy

Bioaccumulation: No relevant data found.

White mineral oil (petroleum)

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 5.18 Measured

Molybdenum disulfide

Bioaccumulation: Partitioning from water to n-octanol is not applicable.

Calcium hydroxide

Bioaccumulation: Not applicable

Graphite

Bioaccumulation: Not applicable Not applicable

Mobility in Soil

Butane (containing < 0.1% butadiene)

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 44 - 900 Estimated.

Naphtha (petroleum), hydrotreated heavy

No relevant data found.

White mineral oil (petroleum)

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 510 Estimated.

Molybdenum disulfide

No relevant data found.

Calcium hydroxide

No relevant data found.

Graphite

No relevant data found.

Results of PBT and vPvB assessment

Butane (containing < 0.1% butadiene)

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Naphtha (petroleum), hydrotreated heavy

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

White mineral oil (petroleum)

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Molybdenum disulfide

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Calcium hydroxide

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Graphite

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Other adverse effects**Butane (containing < 0.1% butadiene)**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Naphtha (petroleum), hydrotreated heavy

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

White mineral oil (petroleum)

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Molybdenum disulfide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Calcium hydroxide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Graphite

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

SECTION 14: TRANSPORT INFORMATION

ADG

Proper shipping name	AEROSOLS
UN number	UN 1950
Class	2.1
Packing group	

Classification for SEA transport (IMO-IMDG):

Proper shipping name	AEROSOLS
UN number	UN 1950
Class	2.1
Packing group	
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Aerosols, flammable
UN number	UN 1950
Class	2.1
Packing group	

Hazchem Code

None Allocated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

Poison Schedule

Schedule 5

Product repackaged for public consumer use should be labelled in accordance with the current Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Inventory of Industrial Chemicals (AIIC)

All ingredients in this preparation are listed in the Australian Inventory of Industrial Chemicals, AIIC, or are exempt.

Prohibition/Licensing Requirements : Neither banned nor restricted

SECTION 16: ANY OTHER RELEVANT INFORMATION

Revision

Identification Number: 4045666 / A847 / Issue Date: 11.10.2023 / Version: 5.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
AU OEL	Australia. Workplace Exposure Standards for Airborne Contaminants.
STEL	Short-term exposure limit
TWA	Exposure standard - time weighted average

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and

Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Tulp Operations Australia Pty Ltd urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

AU